



# HARDING

## USER'S MANUAL ENGLISH MOVEMENTS CALIBER

RONDA powertech	RONDA slimtech	RONDA normtech	RONDA mastertech
- 585	- 1005	- 774	- 7002.B
- 505	- 1006	- 775	- 7003.B
- 515	- 1009	- 704	- 7004.B
	- 1015	- 705	
	- 1016	- 784	
	- 1019	- 785	
		- 714	
		- 715	
		- 715Li	

You have decided to buy a watch, which was assembled by a watchmaker using a Ronda movement. Please note that no watches are produced or distributed under the Ronda brand.

In case of repairs, guarantee claims and questions concerning the functioning of a watch, purchasers and consumers should contact their retailer or the watch manufacturer, for which the relevant information can be found in the sales or guarantee documentation provided with the watch.

Cal. 585 / 785:

Battery type: 362 / SR721SW (Ø 7.9 mm x 2.1 mm)

Cal. 774 / 775 / 784:

Battery type: 364 / SR621SW (Ø 6.8 mm x 2.1 mm)

Cal. 505 / 515 / 704 / 705 / 714 / 715:

Battery type: 371 / SR920SW (Ø 9.5 mm x 2.05 mm)

Cal. 6003.D / 6004.D / 6003.B / 6004.B:

Battery type: 373 / SR916SW (Ø 9.5 mm x 1.6 mm)

Cal. 1005 / 1006 / 1009 / 1015 / 1016 / 1019:

Battery type: 341 / SR714SW (Ø 7.9 mm x 1.4 mm)

Cal. 7002.B / 7003.B / 7004.B:


Battery type: 381 / SR1120SW (Ø 11.6 mm x 2.05 mm)

Cal. 715Li:

Battery type: CR 2016 (Ø 20 mm x 1.6 mm)

Precision: +20 / -10 seconds per month

Cal. 585	Cal. 6003.D
Cal. 505	Cal. 6004.D
Cal. 515	Cal. 6003.B
	Cal. 6004.B



**Pos. I** Position of rest (watch running)

**Pos. II** Quick-change correction for date

*The date can also be corrected during the day-changing phase between 10 pm and midnight. The date of the following day has to be set, because no automatic date change takes place at midnight.*

- Pull the crown out to position II (watch still running).
- Turn the crown clockwise until the required date appears.

Cal. 6003.D & 6004.D:

- Turn the crown until the required date appears.
- Push the crown back into position I.

**Pos. III** Setting the time

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.




# HARDING

[www.hardingwatches.com](http://www.hardingwatches.com)



# HARDING

Cal. 774	Cal. 715Li
Cal. 775	
Cal. 704	Cal. 1005
Cal. 705	Cal. 1006
Cal. 784	Cal. 1009
Cal. 785	Cal. 1015
Cal. 714	Cal. 1016
Cal. 715	Cal. 1019



**Pos. I** Position of rest (watch running)

**Pos. II** Quick-change correction for date


*Blocking time for the quick-change day correction is from approx. 9.30 pm and midnight.*

- Pull the crown out to position II (watch still running).
- Turn the crown until the current date appears.
- Push the crown back into position I.

**Pos. III** Setting the time

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.

Cal. 7002.B
Cal. 7003.B
Cal. 7004.B



**Pos. I** Position of rest (watch running)

**Pos. II** Quick-change correction for date

*The date can also be changed during the day-changing phase between approx. 8.00 pm and midnight.*

*The date of the following day has to be set, because no automatic date change takes place at midnight.*

- Pull the crown out to position II (watch still running).
- Turn the crown until the current date appears.
- Push the crown back into position I.

**Pos. III** Setting the time

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.



## HARDING

[www.hardingwatches.com](http://www.hardingwatches.com)